

SERIES 32



70 Shore D



-5° C to +40° C



40 - 60mm



30 - 90kg

Polyamide 6 wheels

- Black nylon wheel
- Suitable for environments where humidity and chemical agents are present
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22881:2004



Available Bore Types



Plain
Bore

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Recommended for use on catering and institutional trolleys with light carrying capacities. Good resistance to chemical agents but not suitable on uneven flooring.

Industries




Food Industry




Furniture

Floor Suitability


Suitable on tiles and resin-cement; not recommended on abrasive, unpaved floors or in presence of processing residues. Not suitable on fragile floor or with obstacles along the path.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 32 CONTINUED



70 Shore D



-5°C to +40°C



40 - 60mm



30 - 90kg

WHEELS



Plain
Bore

						
(mm)	(mm)	(mm)	(mm)	(daN)	(kg)	(code)
40	17	8	21	30	0.02	321102
50	17	8	22	40	0.02	321104
50	22	8	28	50	0.03	321105
60	22	8	28	60	0.03	321106

INSTITUTIONAL SWIVEL CASTORS



										SWIVEL
	40	17	61	42x42	30x30	5	24	30	0.12	324101
	50	17	66	42x42	30x30	5	24	40	0.12	324102
	60	22	83	60x60	45x45	6	21	60	0.22	324103



INSTITUTIONAL FIXED CASTORS

									FIXED
	40	17	61	55x25	42	5	30	0.10	325101
	50	17	66	55x25	42	5	40	0.10	325102
	60	22	83	60x60	45x45	6	60	0.20	325103

INSTITUTIONAL CASTORS WITH THREADED STEM



										BOLT HOLE
	40	17	61	M10	20	35	24	30	0.12	326101
	50	17	66	M10	20	35	24	40	0.14	326102
	60	22	83	M12	24	41	21	60	0.23	326103

INSTITUTIONAL TWIN CASTORS FOR HIGH CARRYING CAPACITY



										SWIVEL		SWIVEL & BRAKE
50	18+18	71	60x60	45x45	6	25.5	83	90	0.28	324302	0.33	328202



30 - 90kg



												
	50	30	71	M10	25	52	25.5	83	80	0.28	326302	0.33