

SERIES 65ER



95 Shore A



-20° C to +80° C



125 - 200mm



450 - 800kg

'TR Roll' polyurethane wheels with ergonomic round profile and aluminium centre

- Excellent rolling resistance and elasticity, highly resistant to wear and tear
- Manual/powered handling applications
- Up to 12km/h with correct bracket
- Suitable for use on compact surfaces
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Ball Bearing



Ball Bearing Facility

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents



Uses

Designed to improve trolleys manual handling under heavy loads. The round profile reduces the start-up coefficient when the castors are positioned at 90° from the line of movement and therefore greatly reduces the amount of effort required by the operators when handling trolleys. Combined with appropriate brackets they guarantee excellent performance for mechanical handling up to 12km/h.

Industries



Airport/
Aerospace




Automotive




Towing/
Mechanical
Handling

Floor Suitability


Suitable for all types of industrial floors, except unpaved; it easily overcomes obstacles.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

SERIES 65ER CONTINUED



95 Shore A



-20°C to +80°C



125 - 200mm



450 - 800kg

WHEELS



Ball
Bearing



Ball Bearing
Facility

(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(daN)	(daN)	(daN)	(kg)	(code)	(kg)	(code)
125	40	20	50	47	14	650	250	450	0.73	652503	0.51	654503
160	50	20	58	47	14.5	900	280	700	1.11	652504	0.89	654504
200	50	20	58	47	14	1000	300	800	1.68	652506	1.44	654506
250	50	20	55	52	15	1200	330	1000	2.40	652508	2.10	654508

MEDIUM DUTY CASTORS - M





										SWIVEL		FIXED		SWIVEL & BRAKE
160	50	199	140x110	105x80	11	58	178	500	2.81	655904	2.10	656004	3.28	656304
200	50	240	140x110	105x80	11	50	178	500	3.52	655906	2.87	656006	3.90	656306

HEAVY DUTY CASTORS - P



										SWIVEL		FIXED		SWIVEL & BRAKE
125	40	170	140x110	105x80	11	70	126	450	2.27	655913	1.63	656013	2.83	656313
160	50	205	140x110	105x80	11	70	126	700	3.46	655914	2.28	656014	4.27	656314
200	50	205	140x110	105x80	11	70	126	750	4.14	655916	2.68	656016	4.74	656316

OPTIONS AVAILABLE TO ORDER



For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 65ER CONTINUED



95 Shore A



-20° C to +80° C



125 - 200mm



450 - 800kg

HEAVY DUTY TOWING CASTORS - PT





	160	50	70	140x110	105x80	11	70	126	700	3.34	SWIVEL	2.28	FIXED	3.97	SWIVEL & BRAKE
	200	50	70	140x110	105x80	11	70	126	800	4.36	655956	2.68	656016	4.89	656356

EXTRA HEAVY DUTY CASTORS - EP



	160	50	205	135x110	105x80	11	70	126	700	3.62	SWIVEL	3.21	FIXED	4.14	SWIVEL & BRAKE
	200	50	250	135x110	105x80	11	70	126	800	4.40	655926	3.96	656026	4.97	656326

OPTIONS AVAILABLE TO ORDER



SERIES 65ER CONTINUED



95 Shore A



-20°C to +80°C



125 - 200mm



450 - 800kg

ELECTRO WELDED CASTORS - EE MHD




	125	40	182	135x110	105x80	11	51	157	450	3.65	SWIVEL	2.67	656033	4.53	656333
	160	50	215	135x110	105x80	11	60	157	700	4.11	655934	3.12	656034	4.99	656334
	200	50	252	135x110	105x80	11	70	157	800	4.8	655936	3.82	656036	6.14	656336

ELECTRO WELDED SPRUNG-LOADED CASTORS EES MHD




	160	50	248	135x110	105x80	11	100	240	700	7.07	SWIVEL	5.82	658504	8.13	659904
	200	50	268	135x110	105x80	11	100	265	800	7.67	657906	6.42	658506	8.78	659906

OPTIONS AVAILABLE TO ORDER



Directional Lock for
brackets d. 150-200mm



Directional Lock for
brackets EE MHD

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk